


# TYČE PRIEREZU ROVNORAMENNÉHO L

valcované za tepla



EN	
EN 10025 / EN 10056	
S235JR	
S355J0, S355J2	


Menovité rozmery				Dĺžka*		Teor. hmotnosť
b	t	r	r1	(mm)		(kg/m)
20	3	3,5	2,0	6 000	12 000	0,880
25	3	3,5	2,0	6 000	12 000	1,110
25	4	3,5	2,0	6 000	12 000	1,450
30	3	5,0	2,5	6 000	12 000	1,360
30	4	5,0	2,5	6 000	12 000	1,780
35	3	5,0	2,5	6 000	12 000	1,800
35	4	5,0	2,5	6 000	12 000	2,090
40	3	6,0	3,0	6 000	12 000	1,840
40	4	6,0	3,0	6 000	12 000	2,420
40	5	6,0	3,0	6 000	12 000	2,970
45	4	7,0	3,5	6 000	12 000	2,740
45	5	7,0	3,5	6 000	12 000	3,380
50	4	7,0	3,5	6 000	12 000	3,060
50	5	7,0	3,5	6 000	12 000	3,770
50	6	7,0	3,5	6 000	12 000	4,470
55	5	8,0	4,0	6 000	12 000	4,180
55	6	8,0	4,0	6 000	12 000	4,950
60	6	8,0	4,0	6 000	12 000	5,420
60	8	8,0	4,0	6 000	12 000	7,090
65	6	9,0	4,5	6 000	12 000	5,910
65	8	9,0	4,5	6 000	12 000	7,730
70	6	10,0	5,0	6 000	12 000	6,400
70	7	10,0	5,0	6 000	12 000	7,390
70	8	10,0	5,0	6 000	12 000	8,370
80	6	10,0	5,0	6 000	12 000	7,340
80	8	10,0	5,0	6 000	12 000	9,630
80	10	10,0	5,0	6 000	12 000	11,860

Menovité rozmery				Dĺžka*		Teor. hmotnosť
b	t	r	r1	(mm)		(kg/m)
90	6	10	5,0	6 000	12 000	8,280
90	8	11	5,5	6 000	12 000	10,890
90	10	11	5,5	6 000	12 000	13,430
100	6	12	6,0	6 000	12 000	9,260
100	8	12	6,0	6 000	12 000	12,180
100	10	12	6,0	6 000	12 000	15,040
100	12	12	6,0	6 000	12 000	17,830
110	8	12	6,0	6 000	12 000	13,430
110	10	12	6,0	6 000	12 000	16,610
120	8	13	6,5	6 000	12 000	14,710
120	10	13	6,5	6 000	12 000	18,200
120	12	13	6,5	6 000	12 000	21,620
130	12	14	7,0	6 000	12 000	23,530
130	14	14	7,0	6 000	12 000	27,200
140	10	15	7,5	6 000	12 000	21,380
140	12	15	7,5	6 000	12 000	25,440
140	14	15	7,5	6 000	12 000	29,420
160	10	17	8,5	6 000	12 000	24,580
160	12	17	8,5	6 000	12 000	29,260
160	14	17	8,5	6 000	12 000	33,870
160	16	17	8,5	6 000	12 000	38,430
180	12	18	9,0	6 000	12 000	33,050
180	14	18	9,0	6 000	12 000	38,300
200	14	18	9,0	6 000	12 000	42,690
200	16	18	9,0	6 000	12 000	48,500
200	20	18	9,0	6 000	12 000	59,930

\* iné dĺžky podľa požiadaviek zákazníka

# TYČE PLOCHÉ

valcované za tepla



EN	
EN 10025 / EN 10058	
S235JR	
S355J0, S355J2	
C45	

Šírka a (mm)	Hrúbka steny h (mm)																	
	5	6	8	10	12	14	15	16	18	20	22	25	30	35	40	45	50	60
Teoretická hmotnosť na 1 m (kg/m)																		
12	0,471	0,565																
14	0,550	0,659	0,879															
16	0,628	0,754	1,000	1,260	1,510													
18	0,707	0,848	1,130	1,410	1,700													
20	0,785	0,942	1,260	1,570	1,884	-	2,360											
25	0,981	1,180	1,570	1,960	2,360		2,940											
30	1,180	1,410	1,880	2,360	2,830	3,300	3,530	3,770	4,240	4,710								
35	1,374	1,650	2,200	2,750	3,300	3,850	4,120	-	-	5,500	-	6,870	8,240					
40	1,570	1,880	2,510	3,140	3,770	4,400	4,710	5,020	5,650	6,280	-	7,850	9,420					
45	1,770	2,120	2,830	3,530	4,240	4,950	5,300	5,650	6,360	7,070	-	8,830	10,600					
50	1,960	2,360	3,140	3,930	4,710	5,500	5,890	6,280	7,070	7,850	-	9,810	11,780	-	-	-	19,620	
55	2,160	2,590	3,450	4,320	5,180	6,050	-	6,910	7,770	8,640	-	10,800	13,000	15,100				
60	2,360	2,830	3,770	4,710	5,650	6,590	7,070	7,540	8,840	9,420	-	11,775	14,130	-	18,840	-		
65	-	-	-	5,100	-	-	-	-	-	-	-	-	-	-	-	-	-	
70	2,750	3,300	4,400	5,500	6,590	7,690	8,240	8,790	9,890	10,990	-	13,700	16,500	-	22,000	-	27,500	
75	2,940	3,530	4,710	5,890	-	-	8,830	-	-	11,800	-	-	-	-	-	-	-	
80	3,140	3,770	5,020	6,280	7,540	8,790	9,420	10,050	-	12,550	-	15,700	18,840	-	25,100	-	31,400	
90	3,530	4,240	5,650	7,070	8,480	9,890	10,600	11,300	-	14,100	-	17,700	21,200	-	28,300	-	35,330	
100	3,930	4,710	6,280	7,850	9,420	11,000	11,780	12,600	14,100	15,700	-	19,630	23,550	-	31,400	-	39,250	47,100
110	4,320	5,180	6,910	8,640	10,400	12,100	-	13,800	-	17,300	-	-	-	-	34,500	-	-	-
120	4,710	5,650	7,540	9,420	11,300	13,200	14,100	15,100	17,000	18,840	-	23,550	-	-	37,680	-	47,100	56,520
130	5,100	6,120	8,160	10,210	12,250	14,300	15,300	16,330	18,400	20,400	-	25,500	30,600	-	-	-	-	-
140	5,500	6,590	8,790	11,000	13,190	-	16,490	17,600	19,800	22,000	-	27,500	33,000	-	-	-	-	-
150	5,890	7,070	9,420	11,780	14,130	16,490	17,670	18,840	21,200	23,550	-	29,440	35,330	-	47,100	-	-	-

Poznámka: Dodanie je možné v dĺžkach 6 m, iné dĺžky podľa požiadavky zákazníka. Po dohode aj iné akosti.